iDesign Model iD1.108-26

ARCHITECTS' AND ENGINEERS' SPECIFICATIONS

The two-way full range loudspeaker system shall incorporate a 2" (51 mm) voice coil, 8" (204 mm) diameter LF transducer and a 1" (25 mm) exit, 1.75" (45 mm) diaphragm compression driver HF transducer. The LF driver shall be mounted in an optimally vented enclosure tuned for maximum low frequency response. The high frequency transducer shall be mounted to a true constant directivity acoustic horn with a nominal horizontal coverage pattern of 120°. The vertical coverage pattern of the horn shall be 60° and shall also provide true constant directivity. The HF horn shall feature a square mounting flange, allowing the horn to be rotated by 90°.

The systems frequency response shall vary no more than ±3 dB from 60 Hz to 18 kHz measured on axis. The low frequency transducer shall produce a Sound Pressure Level (SPL) of 96 dB SPL at a distance of 1 meter with an electrical power input of 1 Watt, and shall be capable of producing a maximum peak output of 127 dB SPL on axis at 1 meter. The high frequency transducer shall produce an acoustic Sound Pressure Level (SPL) of 107 dB SPL on axis at 1 meter with an electrical power input of 1 Watt, and shall be capable of producing a peak output of 132 dB SPL on axis at 1 meter.

The low frequency transducer shall handle 300 Watts of amplifier power (per ref Standard AES2-1984-r2003) and shall have a nominal impedance of 8 Ohms. The high frequency transducer shall handle 100 Watts of amplifier power (per AES ref Standard AES2-1984-r2003) and shall have a nominal impedance of 16 Ohms.

The loudspeaker enclosure shall have a maximum weight of 31 lbs.(14.1 kg) and shall measure 10.97" (279 mm) wide at front, 7.97" (203 mm) in width at rear, 19.19" (488 mm) in height, and 11.5"(292 mm) in depth. The enclosure sides shall taper at 15° from a maximum frontal width, narrowing to the rear. The structure of the enclosure shall be constructed of 12-ply void-free birch hardwood plywood and shall have a weather and wear resistant ProCoat(tm) polyurea hybrid finish.

Input connectors shall be two, four-terminal barrier strips, wired together in parallel. A total of twelve 3/8"-18 UNC threaded mounting/suspension points (four on top, three on bottom, two per side and one back) shall be provided.

Four additional mounting points shall be provided on the top, bottom, and each side configured to accept an Omnimount brand, Series 60 bracket.

Components in the front of the enclosure are to be protected by a curved grill made from perforated steel that is coated with heat cured epoxy powder, and lined with acoustically transparent foam.

The 2-way full range loudspeaker shall be the McCauley Sound model iD1.108-26.

McCauley Sound, Inc. - 16607 Meridian Avenue East - Puyallup, WA 98375 - U.S.A
Call Toll Free: 1.877.McCauley - Fax: 253.841.3050 - http://www.mccauley.com